

TENDER TEXT



CEILING SURFACE LIGHTS

Sunny

LP-ODL451518



TENDER TEXT

Supply and install Sunny (LP-ODL451518) Ceiling Surface Light by LIGHT PLUS UK. Housing: Vandal Resistant & V2 Self Extinguishing Polycarbonate UV Stabilized. Diffuser: Anti Glare with UV Polycarbonate. Beam Angle: 120°. Color Available: White, Black & Dark-Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC110~240 V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. Or equal and approved.

DESCRIPTION

Sunny LED Fixture for illuminating common or outdoor areas near homes, is suitable for indoor and outdoor areas, with ceiling or wall installation where more intense and diffused lighting is required. It is particularly suited for lighting stairs, building entrance areas, corridors in shopping malls, shops, hotels & restaurants. Possibility of customising it by changing the type of light source. The wide range of Mazda LED light sources with LED and CFL sources or even to transform it into emergency lighting.

TECHNICAL CHARACTERISTICS

Housing	Vandal Resistant & V2 Self Extinguishing Polycarbonate UV Stabilized
Diffuser	Anti Glare with UV Polycarbonate
Beam Angle	120°
Color Available	White, Black & Dark-Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC110~240 V

Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL451518	18W	LED	2160lm	A300 X B221 X C40mm
LP-ODL451525	25W	LED	3000lm	A350 X B221 X C40mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.