

TENDER TEXT



CEILING SURFACE LIGHTS

Moon

LP-ODL12



TENDER TEXT

Supply and install Moon (LP-ODL12) Ceiling Surface Light by LIGHT PLUS UK. Housing: High quality PC. Diffuser: Anti Glare with UV Polycarbonate. Beam Angle: 36° / 45° / 60° / 90°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 53C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Our white ceiling mounted luminaire can do it. Moon ceiling light(full PC) adopts elegant and concave design, which makes the luminous surface compact and with magic 3D effects. IP54 rated luminaire is suitable for inside bathroom. Surface mounted and suspended installation are also optional, equipped with rotating lamp fixture, makes the surface mounted installation much easier.

TECHNICAL CHARACTERISTICS

Housing	High quality PC
Diffuser	Anti Glare with UV Polycarbonate
Beam Angle	36° / 45° / 60° / 90°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C° ~ 53C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL12	12W	LED	1440lm	A270 X B70 mm
LP-ODL18	18W	LED	2160lm	A320 X B70 mm
LP-ODL25	25W	LED	3000lm	A320 X B70 mm
LP-ODL30	30W	LED	3600lm	A420 X B85 mm
LP-ODL35	35W	LED	4200lm	A420 X B85 mm
LP-ODL40	40W	LED	4800lm	A420 X B85 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.