

TENDER TEXT



CEILING SURFACE LIGHTS

EDA

LP-ODL341012



TENDER TEXT

Supply and install EDA (LP-ODL341012) Ceiling Surface Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: 94-v0 Fire-rated PC diffuser. Beam Angle: 90° / 120°. Color Available: White, Black & Dark-Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

EDA LED with easy installation and best features. This bulkhead light adopts Die-casting aluminum body and 94-V0 fire-rated PC cover. It is also available as led emergency bulkhead are ideal for applications that require continuous light even after a power outage. Modern IP65 rated led bulkhead also provide high bright lighting to stairway, lobby, reception, corridors and building entrances.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	94-v0 Fire-rated PC diffuser
Beam Angle	90° / 120°
Color Available	White, Black & Dark-Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL341012	12W	LED	1440lm	A250 X B40 mm
LP-ODL341020	20W	LED	2400lm	A250 X B40 mm
LP-ODL341024	24W	LED	2800lm	A250 X B40 mm
LP-ODL341036	36W	LED	4320lm	A300 X B40 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.