

TENDER TEXT



CEILING SURFACE LIGHTS

Pop III

LP-ODL232710



TENDER TEXT

Supply and install Pop III (LP-ODL232710) Ceiling Surface Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 38°. Color Available: White/Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC200~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Pop III Cylinder lamp adopts straightforward design with stylish appearance with high quality COB LED chip with high lumen and pure color. The AL6063 Aluminum radiator in sand blast oxidation treatment provides excellent heat dissipation and corrosion resistance. The built-in power supply with high conversion efficiency is stable and reliable. it is very suitable for star hotel, restaurant, shopping mall, villa, residence and other high-end projects.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	38°
Color Available	White/Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC200~240V
Working Temperature	-20C° ~ 60C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL232710	10W	LED	1200lm	A65 X B120 mm
LP-ODL232715	15W	LED	1800lm	A90 X B140 mm
LP-ODL232720	20W	LED	2400lm	A108 X B170 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.