

TENDER TEXT



CEILING SURFACE LIGHTS

Pop II

LP-ODL232509



TENDER TEXT

Supply and install Pop II (LP-ODL232509) Ceiling Surface Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 15° / 24° / 36° / 45°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Pop-II Cylinder lamp adopts straightforward design with stylish appearance with high quality COB LED chip with high lumen and pure color. The color of surface ring is replaceable, which could create diversified light atmosphere according to different environment. The AL6063 Aluminum radiator in sand blast oxidation treatment provides excellent heat dissipation and corrosion resistance. The built-in power supply with high conversion efficiency is stable and reliable. It is very suitable for star hotel, restaurant, shopping mall, villa, residence and other high-end projects.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	15° / 24° / 36° / 45°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL232509	09W	LED	1080lm	A60 X B150 mm
LP-ODL232512	12W	LED	1440lm	A60 X B150 mm
LP-ODL232515	15W	LED	1800lm	A80 X B150 mm
LP-ODL232518	18W	LED	2160lm	A80 X B180 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.