

TENDER TEXT



CEILING SURFACE LIGHTS

Pop

LP-ODL232607



TENDER TEXT

Supply and install Pop (LP-ODL232607) Ceiling Surface Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Tempered Glass Diffuser. Beam Angle: 20° / 40°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 10. Or equal and approved.

DESCRIPTION

Pop Cylinder lamp adopts straightforward design with stylish appearance with high quality COB LED chip with high lumen and pure color. The AL6063 Aluminum radiator in sand blast oxidation treatment provides excellent heat dissipation and corrosion resistance. The built-in power supply with high conversion efficiency is stable and reliable. it is very suitable for star hotel, restaurant, shopping mall, villa, residence and other high-end projects.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Tempered Glass Diffuser
Beam Angle	20° / 40°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 60C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL232607	07W	LED	840lm	A83 X B125 mm
LP-ODL232609	09W	LED	1080lm	A83 X B125 mm
LP-ODL232615	15W	LED	1800lm	A83 X B125 mm
LP-ODL232625	25W	LED	3000lm	A123 X B156 mm
LP-ODL232635	35W	LED	3000lm	A160 X B183 mm
LP-ODL232645	45W	LED	3000lm	A200 X B212 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.