

TENDER TEXT



FLOOD & SPIKE LIGHTS

Lumi

LP-FL305015



TENDER TEXT

Supply and install Lumi (LP-FL305015) Flood & Spike Light by LIGHT PLUS UK. Housing: Die-cast Aluminum. Diffuser: Tempered Glass. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -25C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Lumi LED Flood Light is an IP66-rated luminaire for lighting landscapes, trees, columns, monuments, and architectural details. It has numerous options, including optics for flood or accent lighting, colour temperatures and a choice of RGB, RGBW or RGBA colour mixing as well as various accessories for bracket installation, spread lenses, and controls. The luminaire also has an anti corrosion option for use in harsh, chemical, or coastal environments.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum
Diffuser	Tempered Glass
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-25C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL305015	15W	LED	1800lm	A158 x B173 x C133mm
LP-FL305022	22W	LED	2640lm	A158 x B173 x C133mm
LP-FL305030	30W	LED	3600lm	A184 x B204 x C141mm
LP-FL305036-RGBW	36W	LED	4320lm	A184 x B204 x C141mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.