

TENDER TEXT



FLOOD & SPIKE LIGHTS

Pure

LP-FL304511



TENDER TEXT

Supply and install Pure (LP-FL304511) Flood & Spike Light by LIGHT PLUS UK. Housing: Die-cast Aluminum. Diffuser: Tempered Glass. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: RAL9023 Pearl Dark Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC110~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. Or equal and approved.

DESCRIPTION

Pure LED Flood Light is an IP66-rated luminaire for lighting landscapes, trees, columns, monuments, and architectural details. It has numerous options, including optics for flood or accent lighting, colour temperatures and a choice of RGB, RGBW or RGBA colour mixing as well as various accessories for bracket installation, spread lenses, and controls. The luminaire also has an anti corrosion option for use in harsh, chemical, or coastal environments.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum
Diffuser	Tempered Glass
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	RAL9023 Pearl Dark Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC110~240V
Working Temperature	-10C° ~ 50C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL304511	11W	LED	1100lm	A140 x B180 x C130mm
LP-FL304520	20W	LED	2000lm	A140 x B180 x C130mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:10.