

TENDER TEXT



FLOOD & SPIKE LIGHTS

Luminex

LP-FL308560



TENDER TEXT

Supply and install Luminex (LP-FL308560) Flood & Spike Light by LIGHT PLUS UK. Housing: Die-casting Aluminum,. Diffuser: LTempered Glass Transparent. Color Available: Grey. Lifespan: >100,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -40C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Beam Angle: 5° / 12° / 20° / 30° / 45° / 60° / asymmetric 10x60° / 15x30°. Or equal and approved.

DESCRIPTION

Luminex LED Flood Light is a patent owned design, fashion and beautiful appearance, adopt isolate structure to fully ensure the satability and long lifespan of LED light with multiway rotate function of round support, spike or pole mounting, available to meet various occasions demands for outdoor projects Light body adopts high pressure Die-casting aluminum, surface with high resistance painting process, high strength tempered glass, resist the impact and friction.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum,
Diffuser	LTempered Glass Transparent
Color Available	Grey
Lifespan	>100,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-40C° ~ 55C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08
Beam Angle	5° / 12° / 20° / 30° / 45° / 60° / asymmetric 10x60° / 15x30°

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL308560	60W	LED	7200lm	A386 X B235 X C66 mm
LP-FL3085100	100W	LED	12000lm	A386 X B235 X C66 mm
LP-FL3085150	150W	LED	18000lm	A386 X B235 X C66 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 01:11.