

TENDER TEXT



FLOOD & SPIKE LIGHTS

Radiant

LP-SL172210



TENDER TEXT

Supply and install Radiant (LP-SL172210) Flood & Spike Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-cast Powder Coating. Diffuser: Clear Froasted, Tempered Glass. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: Bronze Metallic, Black, White. Lifespan: > 100,000 Hours (L90 B50). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -40C° ~ +55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

The Radiant LED flood lights offers the widest variety of mounting options available. For LED flood lights with fashionable appearance, scientific light distribution, efficiency and ECO performance. This is fully visible, and the direction of the light beam can be adjusted. The best economic fit in doorway, yard, garden, landscape, and piers, etc. can be illuminated.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-cast Powder Coating
Diffuser	Clear Froasted, Tempered Glass
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	Bronze Metallic, Black, White
Lifespan	> 100,000 Hours (L90 B50)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-40C° ~ +55C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL172210	10W	LED	1200lm	A90 X B90 X C97mm
LP-SL172215	15W	LED	1800lm	A90 X B90 X C97mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.