

TENDER TEXT



FLOOD & SPIKE LIGHTS

Lumos

LP-FL309507



TENDER TEXT

Supply and install Lumos (LP-FL309507) Flood & Spike Light by LIGHT PLUS UK. Housing: Die-cast Aluminum with anti-corrosive treatment, Polyester powder coating. Diffuser: Tempered Glass. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: Grey. Lifespan: > 100,000 Hours (L90 B50). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: - 40C° ~ +55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. IK: 10. Or equal and approved.

DESCRIPTION

Lumos LED Flood Light is an IP66-rated luminaire for lighting landscapes, trees, columns, monuments, and architectural details. It has numerous options, including optics for flood or accent lighting, colour temperatures and a choice of RGB, RGBW or RGBA colour mixing as well as various accessories for bracket installation, spread lenses, and controls. The luminaire also has an anti-corrosion option for use in harsh, chemical, or coastal environments.

TECHNICAL CHARACTERISTICS

Housing	Die-cast Aluminum with anti-corrosive treatment, Polyester powder coating
Diffuser	Tempered Glass
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	Grey
Lifespan	> 100,000 Hours (L90 B50)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-40C° ~ +55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	66
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL309507	07W	LED	840lm	A82 X B176 X C140 mm
LP-FL309510	10W	LED	120lm	A82 X B176 X C140 mm
LP-FL309515	15W	LED	1800lm	A82 X B176 X C140 mm
LP-FL309520	20W	LED	2400lm	A108 X B216 X C160 mm
LP-FL309530	30W	LED	3600lm	A108 X B216 X C160 mm
LP-FL309550	50W	LED	6000lm	A108 X B216 X C160 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.