


TENDER TEXT



FLOOD & SPIKE LIGHTS

MVS

LP-FL3050150



TENDER TEXT

Supply and install MVS (LP-FL3050150) Flood & Spike Light by LIGHT PLUS UK. Housing: Die-casting Aluminum. Diffuser: PMMA. Beam Angle: 15° / 24° / 36° / 45°. Color Available: RAL 5008 Gray Blue. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

MVS LED Flood Lights are broad-beamed, high-intensity artificial lights. They are often used to illuminate outdoor playing fields while an outdoor sports event is being held during low-light conditions. The white beam of light produced by it is very much similar to daylight. When used in stadiums, it makes the spectators feel as though it is day time. MVS LED Flood Lights are impervious to temperature fluctuations and environmental conditions. Unlike some other lights, LEDs remain stable & functional even in freezing conditions. This makes them all the more ideal for cold warehouses and storage areas. Being free of Mercury, Lead and Carbon Emissions, MVS LED Flood Lights do not give out any harmful emissions such as carbon. As a result, they are much friendlier to the environment and also to the health of people nearby. What's more, they do not emanate heat and conserve the maximum amount of electricity, which also leads to longevity and safety. It is of IP Rate 67, which means its excellent performance in waterproof, Energy Friendly. LED flood lights eliminate the need for frequent bulb replacements, and you can save as much as 80% on electricity costs, Unaffected by Weather and Temperature Changes. Bold LED flood lights are impervious to temperature fluctuations and environmental conditions.

TECHNICAL CHARACTERISTICS

Housing	Die-casting Aluminum
Diffuser	PMMA

Beam Angle	15° / 24° / 36° / 45°
Color Available	RAL 5008 Gray Blue
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL3050150	150W	LED	24000lm	A350 X B240 X C75mm
LP-FL3050200	200W	LED	32000lm	A350 X B240 X C75mm
LP-FL3050300	300W	LED	48000lm	A350 X B240 X C75mm
LP-FL3050400	400W	LED	64000lm	A605 X B240 X C75mm
LP-FL3050600	600W	LED	96000lm	A665 X B315 X C75mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.