

TENDER TEXT



FLOOD & SPIKE LIGHTS

Bold

LP-FL3020150A



TENDER TEXT

Supply and install Bold (LP-FL3020150A) Flood & Spike Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: PMMA. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: RAL 5008 Gray Blue. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Bold LED Flood Lights are broad-beamed, high-intensity artificial lights. They are often used to illuminate outdoor playing fields while an outdoor sports event is being held during low-light conditions. The white beam of light produced by it is very much similar to daylight. When used in stadiums, it makes the spectators feel as though it is day time. Bold LED Flood Lights are impervious to temperature fluctuations and environmental conditions. Unlike some other lights, LEDs remain stable & functional even in freezing conditions. This makes them all the more ideal for cold warehouses and storage areas. Being free of Mercury, Lead and Carbon Emissions, Bold LED Flood Lights do not give out any harmful emissions such as carbon. As a result, they are much friendlier to the environment and also to the health of people nearby. What's more, they do not emanate heat and conserve the maximum amount of electricity, which also leads to longevity and safety. It is of IP Rate 67, which means its excellent performance in waterproof, Energy Friendly. LED flood lights eliminate the need for frequent bulb replacements, and you can save as much as 80% on electricity costs, Unaffected by Weather and Temperature Changes. Bold LED flood lights are impervious to temperature fluctuations and environmental conditions.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	PMMA

Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	RAL 5008 Gray Blue
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL3020150A	150W	LED	27000lm	A350 x B240 x C75 mm
LP-FL3020200A	200W	LED	36000lm	A350 x B240 x C75 mm
LP-FL3020300A	300W	LED	54000lm	A350 x B240 x C75 mm
LP-FL3020400A	400W	LED	72000lm	A605 x B240 x C75 mm
LP-FL3020600A	600W	LED	108000lm	A605 x B240 x C75 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.