

TENDER TEXT



FLOOD & SPIKE LIGHTS

Frank

LP-FL306722



TENDER TEXT

Supply and install Frank (LP-FL306722) Flood & Spike Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: PMMA with Glass Cover. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -10C° ~ 50C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 66. Or equal and approved.

DESCRIPTION

Frank LED Flood Light is the family of neat products designed for fast and easy installation and with a 5 year guarantee. Frank Flood light is the new range of compact LED spot die-cast aluminium. It is the best solution for architectural lighting, both for indoor and outdoor, able to combine quality lighting, energy saving and low maintenance.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	PMMA with Glass Cover
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-10C° ~ 50C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL306722	22W	LED	2640lm	A235 X B175 X C42 mm
LP-FL306730	30W	LED	3600lm	A235 X B175 X C42 mm
LP-FL306736	36W	LED	4320lm	A235 X B175 X C42 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 05:18.