

TENDER TEXT



FLOOD & SPIKE LIGHTS

Broad

LP-FL306020



TENDER TEXT

Supply and install Broad (LP-FL306020) Flood & Spike Light by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: PMMA with Glass Cover. Beam Angle: 15° / 24° / 36° / 45° / 60° / 90° / 120°. Color Available: Black, White & Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -30C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Broad LED Flood Light is a cost-effective solution, with full range of wattage and optional light distribution, Broad is available for multiple applications. Multiple light distributions for different applications even for stadium and billboard. It can also be used as street light with slip fitter mounting accessory.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	PMMA with Glass Cover
Beam Angle	15° / 24° / 36° / 45° / 60° / 90° / 120°
Color Available	Black, White & Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-30C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL306020	20W	LED	3600lm	A220 X B160 X C87 mm
LP-FL306030	30W	LED	5400lm	A220 X B160 X C87 mm
LP-FL306050	50W	LED	9000lm	A220 X B160 X C87 mm
LP-FL306080	80W	LED	14400lm	A357 X B270 X C71 mm
LP-FL3060100	100W	LED	18000lm	A357 X B270 X C71 mm
LP-FL3060150	150W	LED	27000lm	A408 X B309 X C71 mm
LP-FL3060200	200W	LED	36000lm	A408 X B309 X C71 mm
LP-FL3060300	240W	LED	43200lm	A481 X B372 X C71 mm
LP-FL3060240	300W	LED	54000lm	A481 X B372 X C71 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 08:27.