

TENDER TEXT



WALL RECESSED

Straight

LP-STL359012



TENDER TEXT

Supply and install Straight (LP-STL359012) Wall Recessed by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 24° / 36°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Straight LED Surface wall step light with easy installation, this light adopts die-cast aluminum body. This wall step ideal Applications that require continuous stairway, lobby, reception, corridors etc. light good to provide high bright lighting to stairway, lobby, reception, corridors, etc.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 24° / 36°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STL359012	12W	LED	1440lm	A300 X B55 X C80mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.