


TENDER TEXT



WALL RECESSED

Rocky

LP-STL361006



TENDER TEXT

Supply and install Rocky (LP-STL361006) Wall Recessed by LIGHT PLUS UK. Housing: Die Cast Aluminum. Diffuser: 3mm Tempered Glass. Beam Angle: 15° / 24° / 36°. Color Available: Matt White, Matt Black & Matt Light Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Rocky Light with ideal size and design, this range is suitable for every pedestrian wall, parking ramp and more, it is high quality raw materials ensures high resistance to dust, extraneous corps in general, humidity and water. The LED system is highly efficient to provide excellent luminous flux results in low consumptions. The item presents also features as easy installation and low maintenance requirements.

TECHNICAL CHARACTERISTICS

Housing	Die Cast Aluminum
Diffuser	3mm Tempered Glass
Beam Angle	15° / 24° / 36°
Color Available	Matt White, Matt Black & Matt Light Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STL361006	06W	LED	600lm	A245 X B106 X C260mm
LP-STL361012	12W	LED	1200lm	A245 X B106 X C260mm
LP-STL361015	15W	LED	1500lm	A245 X B106 X C260mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 09:21.