

TENDER TEXT



WALL RECESSED

Bam

LP-STL358001



TENDER TEXT

Supply and install Bam (LP-STL358001) Wall Recessed by LIGHT PLUS UK. Housing: Die-Casting Aluminum with Powder Coating. Diffuser: Optical Lens, Molding Shape Silicon Seal. Beam Angle: 15° / 24°. Color Available: Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Bam LED wall step light with easy installation, this light adopts die-cast aluminum body. This wall step ideal Applications that require continuous stairway, lobby, reception, corridors, etc. Light good to provide high bright lighting to stairway, lobby, reception, corridors etc.

TECHNICAL CHARACTERISTICS

Housing	Die-Casting Aluminum with Powder Coating
Diffuser	Optical Lens, Molding Shape Silicon Seal
Beam Angle	15° / 24°
Color Available	Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	65
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STL358001	01W	LED	120lm	A80 X B57 X C47.5 mm
LP-STL358002	02W	LED	240lm	A80 X B57 X C47.5 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.