


TENDER TEXT



WALL RECESSED

Clory

LP-STL356004



TENDER TEXT

Supply and install Clory (LP-STL356004) Wall Recessed by LIGHT PLUS UK. Housing: Die-Casting Aluminum. Diffuser: Tempered Clear Glass. Beam Angle: 15° / 24° / 36°. Color Available: White, Black & Dark-Gray. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 08. Or equal and approved.

DESCRIPTION

Clory LED wall step light with easy installation, this light adopts die-cast aluminum body. This wall step ideal applications that require continuous stairway, lobby, reception, corridors, etc.

TECHNICAL CHARACTERISTICS

Housing	Die-Casting Aluminum
Diffuser	Tempered Clear Glass
Beam Angle	15° / 24° / 36°
Color Available	White, Black & Dark-Gray
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-STL356004	04W	LED	480lm	105 X 105 X 63.5 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.