

TENDER TEXT



FLOOD & SPIKE LIGHTS

Starry

LP-SL182124



TENDER TEXT

Supply and install Starry (LP-SL182124) Flood & Spike Light by LIGHT PLUS UK. Housing: Aluminum, ABS Plastic spike/Aluminum base. Diffuser: Clear Tempered Glass. Beam Angle: 40°. Color Available: Gray / Black / Single Color. Lifespan: >30,000 Hours (L80 B20). Reflector: Aluminium Reflector. Voltage: 12V, 24V, 220V. Working Temperature: 3000K +-150K >80. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. Or equal and approved.

DESCRIPTION

Starry LED Spike Light is aluminium directional outdoor spike light provides a targeted source of light for illuminating your outdoor areas and features at night. The adjustable black die cast aluminium spotlight has a spiked base for securing it into the ground, and a single light that provides a concentrated beam of light and other options as well attached in the datasheet.

TECHNICAL CHARACTERISTICS

Housing	Aluminum, ABS Plastic spike/Aluminum base
Diffuser	Clear Tempered Glass.
Beam Angle	40°
Color Available	Gray / Black / Single Color
Lifespan	>30,000 Hours (L80 B20)
Reflector	Aluminium Reflector
Voltage	12V, 24V, 220V
Working Temperature	3000K +-150K >80
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL182124	24W	LED	2640lm	A446 X B152 X C120mm
LP-SL182124	24W	LED	2640lm	A215 X B152 X C120mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.