

TENDER TEXT



MAGNETIC SERIES

Pearl

LP-MG11-08



TENDER TEXT

Supply and install Pearl (LP-MG11-08) Magnetic Serie by LIGHT PLUS UK. Beam Angle: 160°. Light Source: SMD LED. CRI: 90. Adjustable: No. Power Factor: 0.9. Input Voltage: DC 48V. IP Rating: IP44. Working Temperature: -10°C~40°C. Color Available: Black / White. Mounting: 48V magnetic track system. Or equal and approved.

DESCRIPTION

Pearl is an opal globe pendant from the LIGHT PLUS Magnetic Series, running on the 48V magnetic track. CRI 90, IP44. Suited to modern workspaces, institutions, small format retail outlets, hotels and high-end villas.

TECHNICAL CHARACTERISTICS

Beam Angle	160°
Light Source	SMD LED
CRI	90
Adjustable	No
Power Factor	0.9
Input Voltage	DC 48V
IP Rating	IP44
Working Temperature	-10°C~40°C
Color Available	Black / White
Mounting	48V magnetic track system

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-MG11-08	8W	LED	800lm	Ø 110 x 1200mm
LP-MG11-16	2x8W	LED	1600lm	Ø 110 x 1200mm
LP-MG11-15	15W	LED	1500lm	Ø 175 x 223mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 05:25.