

TENDER TEXT



FLOOD & SPIKE LIGHTS

Zony

LP-SL182106



TENDER TEXT

Supply and install Zony (LP-SL182106) Flood & Spike Light by LIGHT PLUS UK. Housing: Aluminum, ABS Plastic spike/Aluminum base. Diffuser: Clear Tempered Glass. Beam Angle: 40°. Color Available: Gray / Black (Single Color). Lifespan: >30,000 Hours (L80 B20). Reflector: Aluminium Reflector. Voltage: 12V, 24V, 220V. Beam Angle: 40°. Working Temperature: 3000K ±150K. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. Or equal and approved.

DESCRIPTION

Zony LED Spike Light is aluminium directional outdoor spike light provides a targeted source of light for illuminating your outdoor areas and features at night. The adjustable black die cast aluminium spotlight has a spiked base for securing it into the ground, and a single light that provides a concentrated beam of light and other options as well attached in the datasheet.

TECHNICAL CHARACTERISTICS

Housing	Aluminum, ABS Plastic spike/Aluminum base
Diffuser	Clear Tempered Glass
Beam Angle	40°
Color Available	Gray / Black (Single Color)
Lifespan	>30,000 Hours (L80 B20)
Reflector	Aluminium Reflector
Voltage	12V, 24V, 220V
Beam Angle	40°

Working Temperature	3000K ±150K
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL182106	06W	LED	660lm	A344 X B118 X C90 mm
LP-SL182106	06W	LED	660lm	A344 X B118 X C90 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.