

TENDER TEXT



FLOOD & SPIKE LIGHTS

Spiky

LP-SKL401503



TENDER TEXT

Supply and install Spiky (LP-SKL401503) Flood & Spike Light by LIGHT PLUS UK. Housing: Material Die-casting Alumenium. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 25° / 36°. Color Available: Antique Brass & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -20C° ~ 25C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Spiky LED Garden spike lights are flexible in installation; it can fit into any outdoor environment. LED garden spikes are LED garden lights that are placed in the ground with the fixture above the ground. This is fully visible and can be tilted, so that the direction of the light beam can be adjusted. In this way, objects such as statues, fountains, façades, walkways or ponds can be illuminated. The mounting bracket is designed to fit our spike lights, enabling them to be surface mounted.

TECHNICAL CHARACTERISTICS

Housing	Material Die-casting Alumenium
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 25° / 36°
Color Available	Antique Brass & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-20C° ~ 25C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL401503	3x1W	LED	360lm	A92 x B195 x C67 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.