

TENDER TEXT



FLOOD & SPIKE LIGHTS

Himi

LP-SKL402013



TENDER TEXT

Supply and install Himi (LP-SKL402013) Flood & Spike Light by LIGHT PLUS UK. Housing: Material Die-casting Aluminium. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 25° / 36°. Color Available: Antique Brass & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Himi LED Spike Light is aluminium directional outdoor spike light provides a targeted source of light for illuminating your outdoor areas and features at night. The adjustable black die cast aluminium spotlight has a spiked base for securing it into the ground, and a single light that provides a concentrated beam of light and other options as well attached in the datasheet.

TECHNICAL CHARACTERISTICS

Housing	Material Die-casting Aluminium
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 25° / 36°
Color Available	Antique Brass & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL402013	13x1W	LED	1560lm	A458 x B243 x C145 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.