

TENDER TEXT



FLOOD & SPIKE LIGHTS

Walker

LP-SKL402512



TENDER TEXT

Supply and install Walker (LP-SKL402512) Flood & Spike Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-casting. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 25° / 36°. Color Available: Antique Brass & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC100~240V. Working Temperature: -20°C ~ 55°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

The Walker LED garden spike lights are timeless in design and fit into any outdoor environment. LED spikes are LED lights that are placed in the ground with the fixture above the ground. This is fully visible and can be tilted, so that the direction of the light beam can be adjusted. In this way, objects such as statues, fountains, façades, walkways or ponds can be illuminated.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-casting
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 25° / 36°
Color Available	Antique Brass & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC100~240V
Working Temperature	-20°C ~ 55°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL402512	COB 12W	LED	1440lm	A455 X B150 X C105 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.