

TENDER TEXT



FLOOD & SPIKE LIGHTS

Park

LP-SKL407507



TENDER TEXT

Supply and install Park (LP-SKL407507) Flood & Spike Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-casting. Diffuser: Clear Frosted Glass, Silicon Rubber Gasket. Beam Angle: 15° / 25° / 36°. Color Available: Dark Grey & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC 100~240V. Working Temperature: -20C° ~ 55C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Park LED Spike light is an ideal choice for illuminating flowers, trees, walls and borders. We offer low voltage spike lights with fully adjustable head for tilt and rotation to illuminate items of interest in your garden. So you do not need extra tools because these spike lights are designed for easy installation and adjustment.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-casting
Diffuser	Clear Frosted Glass, Silicon Rubber Gasket
Beam Angle	15° / 25° / 36°
Color Available	Dark Grey & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC 100~240V
Working Temperature	-20C° ~ 55C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-SKL407507	COB 07W	LED	840lm	315 X 150 mm
LP-SKL407510	COB 10W	LED	1200lm	315 X 150 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.