

TENDER TEXT



FLOOR LIGHTS

RADIUS

LP-UL657602



TENDER TEXT

Supply and install RADIUS (LP-UL657602) Floor Light by LIGHT PLUS UK. Housing: Made of 6063 Aluminum body & #316L SUS, T=3.0mm Glass. Diffuser: Frosted Glass. Beam Angle: 10° / 15° / 24° / 36° / 55° / 10° * 60°. Reflector: PMMA Optical Lens. Color Available: Dark Grey, Coal Ash Finish to Customize. Lifespan: >50,000 Hours (L90 B10). Voltage: AC 220~240V / DC 24V. Working Temperature: -15C° ~ +45C°. Accessories: Honeycomb lovre, Antiglare grille. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

The Radius series is IP 67 rated (fully submersible) and is a great choice for underwater lighting of water features and ponds due to its solid plate. The fixture is recessed under. This high quality product can be used in water.

TECHNICAL CHARACTERISTICS

Housing	Made of 6063 Aluminum body & #316L SUS, T=3.0mm Glass
Diffuser	Frosted Glass
Beam Angle	10° / 15° / 24° / 36° / 55° / 10° * 60°
Reflector	PMMA Optical Lens
Color Available	Dark Grey, Coal Ash Finish to Customize
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC 220~240V / DC 24V
Working Temperature	-15C° ~ +45C°
Accessories	Honeycomb lovre, Antiglare grille

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions	Cut Out
LP-UL657602	02W	LED	160lm	A32XB60 mm	A29XB70
LP-UL657604	04W	LED	320lm	A42XB75 mm	A37XB85
LP-UL657605	05W	LED	400lm	A50XB75 mm	A46XB85
LP-UL657607	07W	LED	560lm	A65XB90 mm	A58XB105
LP-UL657610	10W	LED	800lm	A80XB100 mm	A76XB115
LP-UL657615	15W	LED	1200lm	A100XB116 mm	A88XB135

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.