


TENDER TEXT



FLOOR LIGHTS

ECLIPSE

LP-UL657504



TENDER TEXT

Supply and install ECLIPSE (LP-UL657504) Floor Light by LIGHT PLUS UK. Housing: Made of high corrosion die cast aluminum with high corrosion stainless steel 316 trim cover. sealed with silicon gasket rubber. Diffuser: Tempered Glass (L90 B10). Beam Angle: 06° / 13° / 20° / 30° / 120°. Reflector: PMMA Optical Lens. Color Available: SS 316. Lifespan: >50,000 Hours (L90 B10). Voltage: 220~240V. Working Temperature: -20C° ~ +65C°. Accessories: Stainless Steel chain for hanging, ceiling recessed clips, ground recessed PVC Box, honeycomb, front glass for flood beam. Adjustable: Yes. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Round luminaire for installation in-ground-recessed ceiling recessed, ceiling suspended. Die-cast aluminum structure and heat sink. 316L high corrosion stainless steel outer frame. Glass diffuser: transparent with silkscreen border. Double layer coating for high resistance to corrosion: the aluminum components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminum fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint.

TECHNICAL CHARACTERISTICS

Housing	Made of high corrosion die cast aluminum with high corrosion stainless steel 316 trim cover. sealed with silicon gasket rubber.
Diffuser	Tempered Glass (L90 B10)
Beam Angle	06° / 13° / 20° / 30° / 120°
Reflector	PMMA Optical Lens

Color Available	SS 316
Lifespan	>50,000 Hours (L90 B10)
Voltage	220~240V
Working Temperature	-20C° ~ +65C°
Accessories	Stainless Steel chain for hanging, ceiling recessed clips, ground recessed PVC Box, honeycomb, front glass for flood beam
Adjustable	Yes
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL657504	04W	LED	440lm	Ø135 x B126mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.