

TENDER TEXT



FLOOD & SPIKE LIGHTS

Brighton

LP-FL302836



TENDER TEXT

Supply and install Brighton (LP-FL302836) Flood & Spike Light by LIGHT PLUS UK. Housing: 6063 Aluminium Alloy. Diffuser: Toughened Glass. Beam Angle: 30° / 15° x 60°. CRI: ?80. Colour Temperature: 3000K / 6000K / RGB. Light Source: Philips LED. Mounting: Surface. Voltage: AC220-240V. Working Temperature: -15°C ~ +50°C. IP Rating: 65. Lifespan: 50,000 Hours. LED Driver: MEAN WELL, 85% efficiency, 3kV surge protection. Dimming: 1-10V / PWM / DALI. Or equal and approved.

DESCRIPTION

Brighton is a one metre linear wall washer for grazing stone, brick and textured facades. A 6063 aluminium body with a toughened glass front, IP65 for outdoor use, with a 30° beam or an asymmetric 15° x 60° optic. Philips LEDs and a MEAN WELL driver with 3kV surge protection, dimmable on 1-10V, PWM or DALI.

TECHNICAL CHARACTERISTICS

Housing	6063 Aluminium Alloy
Diffuser	Toughened Glass
Beam Angle	30° / 15° x 60°
CRI	?80
Colour Temperature	3000K / 6000K / RGB
Light Source	Philips LED
Mounting	Surface
Voltage	AC220-240V
Working Temperature	-15°C ~ +50°C
IP Rating	65

Lifespan	50,000 Hours
LED Driver	MEAN WELL, 85% efficiency, 3kV surge protection
Dimming	1-10V / PWM / DALI

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL302836	36W	LED		A1000 x B50 x C30mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:24.