

TENDER TEXT



FLOOR LIGHTS

Focus

LP-UL657012



TENDER TEXT

Supply and install Focus (LP-UL657012) Floor Light by LIGHT PLUS UK. Housing: Die-Casting, Grey Paint Powder Coated Aluminum and 316 Stainless Steel. Diffuser: 316 Stainless Steel. Beam Angle: 05° / 10° / 15° / 30° / 45° / 60°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. Heavy Duty: 2000 KG. IK: 10. Or equal and approved.

DESCRIPTION

Luminaire for floor/ground and ceiling installation, fixed, single adjustable versions for different applications, lighting head can be mechanically adjusted without opening the luminaire, high level of flexibility in terms of lighting control, very low glare rating with the deep recessed lighting head, die-casting aluminum body, 316L SS outer trim, 8mm thick tempered glass, very low thermal build-up at the diffuser end, integrated driver, optional versions available with frosted diffuser and 24Vdc models.

TECHNICAL CHARACTERISTICS

Housing	Die-Casting, Grey Paint Powder Coated Aluminum and 316 Stainless Steel
Diffuser	316 Stainless Steel
Beam Angle	05° / 10° / 15° / 30° / 45° / 60°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
Heavy Duty	2000 KG
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL657012	12W	LED	1440lm	A172 X B137 X C145mm
LP-UL657016	16W	LED	1920lm	A172 X B137 X C145mm
LP-UL657027	27W	LED	3240lm	A172 X B137 X C145mm
LP-UL657036	36W	LED	4320lm	A172 X B137 X C145mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.