

TENDER TEXT



FLOOR LIGHTS

Steel

LP-UL217515



TENDER TEXT

Supply and install Steel (LP-UL217515) Floor Light by LIGHT PLUS UK. Housing: Stainless Steel. Diffuser: Front Cover Stainless Steel & Gasket Molding Shape Silicon Seal. Beam Angle: 15° / 24° / 36°. Color Available: Grey. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

Steel Floor Light waterproof IP67 stainless steel 3 l 6L in-ground High Power LED recessed luminaire with round cover plate and clear glass provided Diffusion. Submersible projector to be recessed into the ground inside or outside using the latest high power LED technology. Symmetrical light distribution with several powers and diffusion angles available. It is a robust construction in anodized aluminum body a cover plate in 3 l 6L stainless steel with 4mm thick. HPL Bolas combines high efficiency and long life and luminosity comparable to Ip the other type of floor light. Installed individually or in groups, it is an attractive solution for many facilities in the private or public sector.

TECHNICAL CHARACTERISTICS

Housing	Stainless Steel
Diffuser	Front Cover Stainless Steel & Gasket Molding Shape Silicon Seal
Beam Angle	15° / 24° / 36°
Color Available	Grey
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL217515	15W	LED	1800lm	A120 x B110 mm
LP-UL217520	20W	LED	2400lm	A180 x B110 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.