

TENDER TEXT



FLOOR LIGHTS

FAM

LP-UL654001



TENDER TEXT

Supply and install FAM (LP-UL654001) Floor Light by LIGHT PLUS UK. Housing: Aluminum Die-Casting, 316 grade stainless steel cover in 4mm thickness. Diffuser: Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box. Beam Angle: 25° / 38° / 45° / 60°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Fam Floor Up light is waterproof IP67 stainless steel 316L in-ground recessed luminaire fixed directional with round cover plate and clear glass. In-ground luminary to be place inside or outside. This fixture is resistant to high pressures, up to 2500 KG on certain models. Extremely robust construction, this spot can use an LED with a fix or adjustable lamp holder. This quality luminary is manufactured by machining process. The body is in anodized aluminum and the cover plate is stainless steel 316L.

TECHNICAL CHARACTERISTICS

Housing	Aluminum Die-Casting, 316 grade stainless steel cover in 4mm thickness
Diffuser	Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box
Beam Angle	25° / 38° / 45° / 60°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL654001	01W	LED	120lm	A100 X B140 mm
LP-UL654003	03W	LED	360lm	A100 X B140 mm
LP-UL654006	06W	LED	720lm	A100 X B140 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.