

TENDER TEXT



FLOOR LIGHTS

Beta

LP-UL652025



TENDER TEXT

Supply and install Beta (LP-UL652025) Floor Light by LIGHT PLUS UK. Housing: Body in Stainless Steel Die-Casting, Outer Shell in Black Nylon Reinforced Fiberglass. Diffuser: AISI 316L Stainless Steel. Beam Angle: 10° / 20° / 30°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -120C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Beta, In-ground lights are ideally suited for accenting architectural features, facades, sculptures, to highlight trees, foliage and other outdoor garden landscapes. Stainless steel finishes top ring, Aluminium die casting body and clear tough tempered glass. These fixtures can be used around decks, patio areas, pathways or driveways creating a durable and permanent outdoor lighting solution with a modern look. This particular inground light has an adjustable beam direction and impact resistance: IK10 can take up to 2500kg in weight with ingress protection IP67.

TECHNICAL CHARACTERISTICS

Housing	Body in Stainless Steel Die-Casting, Outer Shell in Black Nylon Reinforced Fiberglass
Diffuser	AISI 316L Stainless Steel
Beam Angle	10° / 20° / 30°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-120C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL652025	25W	LED	3000lm	A260 X B260 mm
LP-UL652030	30W	LED	3600lm	A260 X B260 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.