

TENDER TEXT



FLOOR LIGHTS

Stary

LP-UL207808



TENDER TEXT

Supply and install Stary (LP-UL207808) Floor Light by LIGHT PLUS UK. Housing: Stainless Steel. Diffuser: Front Cover Stainless Steel & Gasket Molding Shape Silicon Seal. Beam Angle: 15° / 24° / 36°. Color Available: Grey. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 08. Or equal and approved.

DESCRIPTION

The UNXR series is IP68 rated (fully submersible) and is a great choice for underwater lighting of water features and ponds due to its solid plate. The fixture is recessed under. This high quality product can be used in water.

TECHNICAL CHARACTERISTICS

Housing	Stainless Steel
Diffuser	Front Cover Stainless Steel & Gasket Molding Shape Silicon Seal
Beam Angle	15° / 24° / 36°
Color Available	Grey
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL207808	08W	LED	960lm	A173 x B77 mm
LP-UL207812	12W	LED	1440lm	A186 x B92 mm
LP-UL207815	15W	LED	1800lm	A186 x B92 mm
LP-UL207824	24W	LED	2800lm	A200 x B92 mm
LP-UL207832	32W	LED	3800lm	A200 x B92 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.