

TENDER TEXT



FLOOR LIGHTS

Upper

LP-UL651012



TENDER TEXT

Supply and install Upper (LP-UL651012) Floor Light by LIGHT PLUS UK. Housing: Body in Aluminium Die-Casting, 316 Grade Stainless Steel Cover in 4mm Thickness. Diffuser: Tempered Clear/Frosted Glass in 8mm Thickness Silicon Rubber Gasket/ Recessed Plastic. Beam Angle: 15° / 24° / 25° / 38°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Upper light is IP67 lighting fixtures with built-in AC220 ~ 240V power supply and a heat dissipating body made of thermally conductive techno polymer that guarantees excellent resistance to corrosion even in harsh (saline) environments. The AISI 316L stainless steel trim and screen in transparent, tempered extra-clear glass guarantee impact and scratch resistance (IK10). Corso is also drive-over up to 2000 kg, perfect for areas with a lot of vehicle traffic.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminium Die-Casting, 316 Grade Stainless Steel Cover in 4mm Thickness
Diffuser	Tempered Clear/Frosted Glass in 8mm Thickness Silicon Rubber Gasket/ Recessed Plastic
Beam Angle	15° / 24° / 25° / 38°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL651012	12W	LED	1200lm	A200 X B235 mm
LP-UL651015	15W	LED	1500lm	A200 X B235 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.