

TENDER TEXT



FLOOR LIGHTS

Wally

LP-UL653703



TENDER TEXT

Supply and install Wally (LP-UL653703) Floor Light by LIGHT PLUS UK. Housing: Made of 316 Stainless Steel. Diffuser: Tempered Glass Diffuser. Beam Angle: 15° / 30° / 45° / 60°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Wally Recessed for outdoor applications, drive-over up to 2500 kg, recessed ground body in aluminium, trim in AISI 316L stainless steel or aluminium, screen in tempered, transparent extra-clear glass, screen in tempered, serigraphed extra-clear glass (diffuse optics) finishes stainless steel, ingress protection: IP67 impact resistance: IK10.

TECHNICAL CHARACTERISTICS

Housing	Made of 316 Stainless Steel
Diffuser	Tempered Glass Diffuser
Beam Angle	15° / 30° / 45° / 60°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V
Working Temperature	-20C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW

IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL653703	3*1W	LED	360lm	A100 x B108mm
LP-UL653709	9*1W	LED	1080lm	A160 x B110mm
LP-UL653718	18*1W	LED	2160lm	A210 x B120mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.