

TENDER TEXT



FLOOR LIGHTS

Opo

LP-UL653507



TENDER TEXT

Supply and install Opo (LP-UL653507) Floor Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-Casting, 304 grade Stainless steel cover in 4mm Thickness. Diffuser: Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box. Beam Angle: 15° / 25° / 38° / 45° / 60°. Color Available: Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Compact drive-over and walk over inground Opo LED luminaire designed for illuminating building facades, green areas, parks and outdoor facilities. With the use of high-power LEDs, the in-ground light range provides high luminosity at a low power consumption. Adapting a double insulation method, all in-ground lights have an IP67 ranking featuring thick tempered glass. Designed to last in extremely harsh environments.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-Casting, 304 grade Stainless steel cover in 4mm Thickness.
Diffuser	Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box
Beam Angle	15° / 25° / 38° / 45° / 60°
Color Available	Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector

Voltage	AC220~240V
Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL653507	07W	LED	840lm	A100 X B140 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.