

TENDER TEXT



FLOOR LIGHTS

Direction

LP-UL855005



TENDER TEXT

Supply and install Direction (LP-UL855005) Floor Light by LIGHT PLUS UK. Housing: Body in Aluminum Die-Casting, 316 Grade Stainless Steel Cover in 4mm Thickness. Diffuser: Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box. Beam Angle: 60° / 90° / 120°. Color Available: White & Black. Lifespan: >50,000 Hours (L90 B10). Reflector: Aluminium Reflector. Voltage: AC220~240V. Working Temperature: -20C° ~ 60C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Direction is a family of outdoor in-ground lights for edge lighting. They are perfect for lighting the edges of paths and other garden elements. They are made of acid-proof Stainless steel and powder coated machined aluminum, lens optical system with Static load resistance 5000 Kg All external screws are in 316 stainless steel. available 1, 2 and 3 Pathway.

TECHNICAL CHARACTERISTICS

Housing	Body in Aluminum Die-Casting, 316 Grade Stainless Steel Cover in 4mm Thickness
Diffuser	Tempered Clear/Frosted Glass in 8mm Thickness, Silicon Rubber Gasket, Recessed Plastic Box
Beam Angle	60° / 90° / 120°
Color Available	White & Black
Lifespan	>50,000 Hours (L90 B10)
Reflector	Aluminium Reflector
Voltage	AC220~240V

Working Temperature	-20C° ~ 60C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL855005	05W	LED	625lm	A116 x B135 x C102mm
LP-UL855008	08W	LED	1000lm	A116 x B135 x C102mm
LP-UL855015	15W	LED	1875lm	A116 x B135 x C102mm
LP-UL855020	20W	LED	2500lm	A116 x B135 x C102mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:13.