

TENDER TEXT



FLOOR LIGHTS

Line

LP-UWL503006



TENDER TEXT

Supply and install Line (LP-UWL503006) Floor Light by LIGHT PLUS UK. Housing: Stainless Steel. Diffuser: Toughened Safety glass. Beam Angle: 15° / 24° / 36° / 45° / 60°. Color Available: RGB / Single. Lifespan: >50,000 Hours (L90 B10). Reflector: Glass Reflector. Voltage: DC24. Working Temperature: -25C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. Or equal and approved.

DESCRIPTION

Line Wall Washer is 24VDC IP67 protected and IK10 linear LED luminaire for indoor and outdoor in-ground installation. It featured Entirely made of stainless steel 316Ti (resistant to corrosion) for lamp housing, built-in aluminum heat sink, frameless design and 15mm thickness frosted tempered glass. Frameless design for two ends of linear luminaire enables Seamless splice installation of numerous fixtures possible. Available in standard length 500mm or 1000mm, or customized length. Suitable for installation into roads, garden and parking lots. It is Anti skid toughened safety glass (ESG)-withstands loads of up to 2500KG. Delivered with male / female IP68 connectors.

TECHNICAL CHARACTERISTICS

Housing	Stainless Steel
Diffuser	Toughened Safety glass
Beam Angle	15° / 24° / 36° / 45° / 60°
Color Available	RGB / Single
Lifespan	>50,000 Hours (L90 B10)
Reflector	Glass Reflector
Voltage	DC24

Working Temperature	-25C° ~ 65C°
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UWL503006	06W	LED	720lm	A500 X B87 X C41 mm
LP-UWL503012	12W	LED	1440lm	A1000 X B87 X C41 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.