

TENDER TEXT



FLOOR LIGHTS

Glossy

LP-UWL504012



TENDER TEXT

Supply and install Glossy (LP-UWL504012) Floor Light by LIGHT PLUS UK. Housing: Entirely Made of Stainless Steel 316Ti 1.4571. Diffuser: Toughened Safety Tempered Glass. Beam Angle: 15° / 24° / 36°. Color Available: Black. Lifespan: 50,000 Hours (L90 B10). Reflector: Glass Reflector. Voltage: DC24V. Working Temperature: -40C° ~ 65C°. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 67. IK: 10. Or equal and approved.

DESCRIPTION

Glossy Wall Washer is 24VDC IP67 protected and IK10 linear LED luminaire for indoor and outdoor in-ground installation. It featured Entirely made of stainless steel 316Ti (resistant to corrosion) for lamp housing, built-in aluminum heat sink. Available in standard length 500mm or 1000mm, or customized length. Suitable for installation into roads, garden and parking lots. it is Anti skid toughened safety glass (ESG)-withstands loads of up to 2500KG. Delivered with male / female IP68 connectors.

TECHNICAL CHARACTERISTICS

Housing	Entirely Made of Stainless Steel 316Ti 1.4571
Diffuser	Toughened Safety Tempered Glass
Beam Angle	15° / 24° / 36°
Color Available	Black
Lifespan	50,000 Hours (L90 B10)
Reflector	Glass Reflector
Voltage	DC24V
Working Temperature	-40C° ~ 65C°

LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	67
IK	10

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UWL504012	12W	LED	780lm	A500 X B95 X C65.4 mm
LP-UWL504024	24W	LED	1560lm	A500 X B95 X C65.4 mm
LP-UWL504035	35W	LED	2275lm	A1000 X B95 X C65.4 mm
LP-UWL504048	48W	LED	3120lm	A1000 X B95 X C65.4 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.