

TENDER TEXT



BOLLARDS

Guild Ford

LP-BL336812



TENDER TEXT

Supply and install Guild Ford (LP-BL336812) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Opal PC. Beam Angle: 116°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

Reliable LED bollard for mixed-use developments and hospitality. The heavy duty construction and UV-stable coating handle heat and sun exposure. Optional sensor packages enable dusk-to-dawn operation or presence-based dimming. All fixings are concealed for a clean finish.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Opal PC
Beam Angle	116°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL336812	12W	LED	705lm	AØ120 X B470 X C800 mm AØ120 X B620 X C1000 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.