

TENDER TEXT



UNDERWATER LIGHTS

Aqua

LP-UL182010



TENDER TEXT

Supply and install Aqua (LP-UL182010) Underwater Light by LIGHT PLUS UK. Housing: Stainless Steel 316L. Diffuser: PMMA Optical Lens with Tempered Glass. Beam Angle: 15° / 30° / 45° / 60°. Color Available: 2700K, 6500K, Red, Green, Blue, Yellow, Amber, RGBW. Lifespan: >50,000 Hours (L80). Voltage: DC24V. Driver Options: On/Off, DALI, Dimmable, Phase Dimming, 1-10V. Working Temperature: +20C° ~ +50C°. Glow Wire Test: 850°. Class: III. IP Rating: 68. IK: 09. Thread: G1 1/2. Or equal and approved.

DESCRIPTION

Aqua is a slim, fully sealed fountain luminaire for 360° fountain-jet lighting, replacing the bulky underwater floodlight. The 316 stainless steel body sits flat around the nozzle, which makes installation and maintenance straightforward. Available in white and coloured light, with RGBW and a choice of drivers.

TECHNICAL CHARACTERISTICS

Housing	Stainless Steel 316L
Diffuser	PMMA Optical Lens with Tempered Glass
Beam Angle	15° / 30° / 45° / 60°
Color Available	2700K, 6500K, Red, Green, Blue, Yellow, Amber, RGBW
Lifespan	>50,000 Hours (L80)
Voltage	DC24V
Driver Options	On/Off, DALI, Dimmable, Phase Dimming, 1-10V
Working Temperature	+20C° ~ +50C°

Glow Wire Test	850°
Class	III
IP Rating	68
IK	09
Thread	G1 1/2

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL182010	10W	9 x SMD LED		A182 x 37 mm
LP-UL182018	18W	9 x SMD LED		A182 x 37 mm
LP-UL182027	27W	9 x SMD LED		A182 x 37 mm
LP-UL182036	36W	9 x SMD LED		A182 x 37 mm
LP-UL182124	24W	12 x SMD LED		A182 x 37 mm
LP-UL182136	36W	12 x SMD LED		A182 x 37 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.