

TENDER TEXT



UNDERWATER LIGHTS

Marina

LP-UL604206



TENDER TEXT

Supply and install Marina (LP-UL604206) Underwater Light by LIGHT PLUS UK. Housing: Extruded Aluminum. Reflector: Aluminum. Diffuser: Clear Tempered Glass. Beam Angle: 20° / 30° / 60° / 80°. CRI: >90. Color Available: 3000K, 4000K, 6000K, RGB, RGBW. Finish: Black, Gray. Color Consistency: SDCM<3. Efficacy: 120 lm/W. Power Factor: 0.9. Lifespan: >50,000 Hours. Voltage: AC220V / DC24V 50/60Hz. Dimming: Triac, 0/1-10V, DALI, DMX. Working Temperature: -20C° ~ +60C°. IP Rating: 68. IK: 08. Or equal and approved.

DESCRIPTION

Marina is a compact linear luminaire with six COB LEDs behind clear tempered glass in an extruded aluminium body, IP68 sealed and IK08 rated. Sections link end to end and hinge to follow curves and corners, with a bracket for surface fixing. Available in white, RGB and RGBW, with Triac, 0/1-10V, DALI and DMX control.

TECHNICAL CHARACTERISTICS

Housing	Extruded Aluminum
Reflector	Aluminum
Diffuser	Clear Tempered Glass
Beam Angle	20° / 30° / 60° / 80°
CRI	>90
Color Available	3000K, 4000K, 6000K, RGB, RGBW
Finish	Black, Gray
Color Consistency	SDCM<3

Efficacy	120 lm/W
Power Factor	0.9
Lifespan	>50,000 Hours
Voltage	AC220V / DC24V 50/60Hz
Dimming	Triac, 0/1-10V, DALI, DMX
Working Temperature	-20C° ~ +60C°
IP Rating	68
IK	08

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL604206	6 x 1W	COB LED	720lm	W42 x H75 x L166 mm
LP-UL604212	6 x 2W	COB LED	1440lm	W42 x H75 x L166 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.