

TENDER TEXT



BOLLARDS

Ripon

LP-BL337210



TENDER TEXT

Supply and install Ripon (LP-BL337210) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear Glass. Beam Angle: 180°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

A square-profile LED bollard with crisp edges and a minimal cap. The sealed module maintains output over time by keeping contaminants out. Symmetric and wide distributions simplify layout across varied path widths. Optional louvers and house-side shields help control spill.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear Glass
Beam Angle	180°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL337210	10W	LED	375lm	A110 X B110 X C400 mm A110 X B110 X C650 mm A110 X B110 X C800 mm A110 X B110 X C1000 mm
LP-BL337215	10W	LED	562lm	A110 X B110 X C400 mm A110 X B110 X C650 mm A110 X B110 X C800 mm A110 X B110 X C1000 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:14.