

TENDER TEXT



BOLLARDS

Luton

LP-BL336208



TENDER TEXT

Supply and install Luton (LP-BL336208) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Opal PC. Beam Angle: 180°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

A versatile LED bollard with a restrained form factor. The light engine offers high efficacy and long service life with integral driver. Choose from forward throw or symmetrical light patterns to optimize spacing. Hardware is stainless steel, and finishes are offered in standard architectural colors.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Opal PC
Beam Angle	180°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL336208	08W	LED	E27	A120 X B120 X C400 mm A120 X B120 X C650 mm A120 X B120 X C800 mm
LP-BL336260	08W	LED	E27	A120 X B120 X C400 mm A120 X B120 X C650 mm A120 X B120 X C800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.