

TENDER TEXT



BOLLARDS

Harrow

LP-BL335710



TENDER TEXT

Supply and install Harrow (LP-BL335710) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear Glass. Beam Angle: 29° / 30°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

A versatile LED bollard with a restrained form factor. The light engine offers high efficacy and long service life with integral driver. Choose from forward throw or symmetrical light patterns to optimize spacing. Hardware is stainless steel, and finishes are offered in standard architectural colors.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear Glass
Beam Angle	29° / 30°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335710	10W	LED	348lm	A120 X B450 mm A120 X B650 mm A120 X B800 mm A120 X B1000 mm
LP-BL335715	15W	LED	536lm	A120 X B850 mm A120 X B1000 mm A120 X B1200 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.