

TENDER TEXT



BOLLARDS

Conventry

LP-BL335110



TENDER TEXT

Supply and install Conventry (LP-BL335110) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Tempered Clear Glass. Beam Angle: 90°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

A clean cylindrical LED bollard that complements modern landscaping. The powder-coated aluminum enclosure resists UV fade and corrosion. Clear, prismatic, or opal optics deliver uniform light with minimal glare. Serviceable gear tray and stainless-steel fasteners make maintenance straight forward.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Tempered Clear Glass
Beam Angle	90°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL335110	10W	LED	562lm	A120 X B400 mm A120 X B680 mm A120 X B1030 mm
LP-BL335115	15W	LED	843lm	A120 X B400 mm A120 X B680 mm A120 X B1030 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 16:31.