

TENDER TEXT



BOLLARDS

Milton

LP-BL334906

TENDER TEXT

Supply and install Milton (LP-BL334906) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear PC. Beam Angle: 120°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 09. Or equal and approved.

DESCRIPTION

Purpose-built LED bollard for parks, promenades, and community walkways. The sealed light engine provides consistent output with low energy use. Multiple height and distribution choices allow spacing flexibility. Optional photocell or motion activation supports adaptive lighting and energy savings.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear PC
Beam Angle	120°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334906	06W	LED	436lm	A190 X B120 X C400 mm A190 X B120 X C650 mm A190 X B120 X C800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:22.