

TENDER TEXT



BOLLARDS

Grove

LP-BL334806



TENDER TEXT

Supply and install Grove (LP-BL334806) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear PC. Beam Angle: 90°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 65. IK: 09. Or equal and approved.

DESCRIPTION

This LED bollard delivers comfortable pathway lighting with restrained glare and clean cut-off. The sealed optic and weather-rated gaskets keep moisture and dust out. Offered with symmetric or forward-throw distributions to keep light where it is needed. Root or surface mounting options simplify installation on new builds or refurbishment.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear PC
Beam Angle	90°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	65

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334806	06W	LED	600lm	AØ140 X B400 mm AØ140 X B650 mm AØ140 X B800 mm
LP-BL334808	08W	LED	800lm	AØ140 X B400 mm AØ140 X B650 mm AØ140 X B800 mm
LP-BL334810	10W	LED	1000lm	AØ140 X B400 mm AØ140 X B650 mm AØ140 X B800 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:21.