

TENDER TEXT



BOLLARDS

Shoreline

LP-BL334710



TENDER TEXT

Supply and install Shoreline (LP-BL334710) Bollard by LIGHT PLUS UK. Housing: Die-Cast Aluminum and Extruded Aluminum Pole. Diffuser: Clear PC. Beam Angle: 120°. Color Available: Black & Grey. Lifespan: >50,000 Hours (L90 B10). Voltage: AC220~240V. Working Temperature: -20°C~+65°C. LED Driver: Light Plus, TriDonic, PHILIPS, OSRAM, MW. IP Rating: 54. IK: 09. Or equal and approved.

DESCRIPTION

An architectural LED bollard that balances performance and durability. The finless, die-cast body manages heat effectively and keeps the profile simple. Optical choices include opal for diffuse light or clear with internal baffles for greater visual control. Rated IP65 and IK10, with tamper-resistant fixings for public spaces.

TECHNICAL CHARACTERISTICS

Housing	Die-Cast Aluminum and Extruded Aluminum Pole
Diffuser	Clear PC
Beam Angle	120°
Color Available	Black & Grey
Lifespan	>50,000 Hours (L90 B10)
Voltage	AC220~240V
Working Temperature	-20°C~+65°C
LED Driver	Light Plus, TriDonic, PHILIPS, OSRAM, MW
IP Rating	54

ITEM CODES

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL334710	10W	LED	402lm	AØ250 X B650 mm
LP-BL334720	20W	LED	402lm	AØ250 X B800 mm
LP-BL334725	25W	LED	600lm	AØ250 X B1000 mm

ACCESSORIES

None

Light Plus UK Limited · Dept 6314, 43 Owston Road, Carcroft, Doncaster DN6 8DA, England · info@lightplus.uk

Specifications subject to change without prior notice. Generated 2026-09-23, 15:23.